

ULTRACLEAN FABRIC (PE)			
Specifications	100% Polyester with ECF strip		
Colour range	Blue (BP), White (WP), Navy (NP), Lemon (LP)		
Unit Weight	106 g/m ²		
Water Vapour Transmission Rate	62.72 g/hrs m ²		
Air Permeability	2.6 cm ² /cm ² /s (toward airflow) 2.2 cm ² /cm ² /s (away from airflow)		
Abrasion Resistance	91,250 cycles		
PARTICLE SHEDDING (HELMKE)	0.3um	0.5um	
Particles/min (0 washes)	2,093.92	2,185.00	
Cleanliness Category	II	II	
Particles/min (250 washes)	150.59	207.60	
Cleanliness Category	I	I	
FILTRATION EFFICIENCY (%)	0.3um	0.5um	5.0um
0 washes	76.96	89.05	92.63
25 washes	84.63	96.90	100
50 washes	80.68	88.52	92.96
75 washes	86.71	93.26	83.33
100 washes	81.11	90.06	85.72
125 washes	90.28	94.01	100
150 washes	84.79	93.41	100
175 washes	86.21	95.62	100
200 washes	80.97	92.50	58.83
225 washes	83.57	95.45	100
250 washes	78.65	86.06	NA

DURACLEAN FABRIC (PE)				
Specifications	100% Polyester with ECF strip			
Unit Weight	109 g/m ²			
Water Vapour Transmission Rate	3.24 mg/hr/cm ²			
Air Permeability	9.8 ml/m ²			
Abrasion Resistance	Good			
Flammability Index	14 (Range 0-100/least to most flammable)			
Melting Point	250 °C			
SURFACE RESISTIVITY (ESD)				
0 washes	10° Ohms per square			
FILTRATION EFFICIENCY (%)	0.5um	0.7um	1.0um	5.0um
0 washes	15%	17%	19%	60%